

Electronic Overhead Stirrers



	EUROSTAR 200 digital control	EUROSTAR 400 digital control
Technical data	replaces EUROSTAR control-visc P4	
Stirring quantity max. (H ₂ O)	100 l	150 l
Max. viscosity	100,000 mPas	100,000 mPas
Motor rating input / output	130 / 84 W	220 / 176 W
Speed range	0/6 – 2000 rpm	0/6 – 2000 rpm
Max. torque at stirring shaft	200 Ncm	400 Ncm
Temp. sensor connection	no PT 1000	no PT 1000
Chuck range	0.5 – 10 mm	0.5 – 10 mm
Dimensions (W x D x H)	91 x 209 x 274 mm 91 x 231 x 297 mm	114 x 245 x 300 mm 114 x 268 x 320 mm
Weight	4.6 kg 4.9 kg	7.8 kg 8.2 kg
Permissible ambient temp.	5 – 40 °C	5 – 40 °C
Permissible relative moisture	80%	80%
Protection class DIN EN 60529	IP 40	IP 40
	Ident. No. 0003990000 Ident. No. 0003992000*	Ident. No. 0004214000 Ident. No. 0004214100*



	EUROSTAR 20 high speed digital control	EUROSTAR 200 control P4
Technical data	replaces EUROSTAR power control-visc 6000	replaces EUROSTAR control-visc P7
Stirring quantity max. (H ₂ O)	20 l	100 l
Max. viscosity	10,000 mPas	150,000 mPas
Motor rating input / output	176 / 125 W	134 / 76 W
Speed range	0/150 – 6000 rpm	0/4 – 530 rpm
Max. torque at stirring shaft	20 Ncm	660 Ncm
Temp. sensor connection	no PT 1000	PT 1000
Chuck range	fixed	0.5 – 10 mm
Dimensions (W x D x H)	86 x 208 x 325 mm 86 x 230 x 325 mm	91 x 230 x 379 mm
Weight	5.3 kg 4.7 kg	5.8 kg
Permissible ambient temp.	5 – 40 °C	5 – 40 °C
Permissible relative moisture	80%	80%
Protection class DIN EN 60529	IP 40	IP 40
	Ident. No. 0004028600 Ident. No. 0025001314*	Ident. No. 0004090000*

* H 67.60 temperature sensor and WH 11 WiCo holder included in the delivery of all EUROSTAR control devices

Accessories starting page 36 - 41